

# ctys-config(1)

lists and exits configuration files

March 10, 2011

## Contents

<b>1</b>	<b>NAME</b>	<b>2</b>
<b>2</b>	<b>SYNTAX</b>	<b>2</b>
<b>3</b>	<b>REMARK</b>	<b>2</b>
<b>4</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>5</b>	<b>OPTIONS</b>	<b>2</b>
<b>6</b>	<b>ARGUMENTS</b>	<b>3</b>
<b>7</b>	<b>EXIT-VALUES</b>	<b>3</b>
<b>8</b>	<b>SEE ALSO</b>	<b>4</b>
<b>9</b>	<b>AUTHOR</b>	<b>4</b>
<b>10</b>	<b>COPYRIGHT</b>	<b>4</b>

## 1 NAME

**ctys-config** - lists and edits configuration files

## 2 SYNTAX

**ctys-config**

```
[-d <level>]
[-D <deepness-level>]
[-e [<group-list>|<path-list>]]
[-F]
[-h]
[-H <help-options>]
[-S]
[-V]
[-X]
[<configfile-list>]
```

## 3 REMARK

This utility is for now alpha release, and may have some gaps.

## 4 DESCRIPTION

**ctys-config** lists and displays configuration files.

The display can be applied for specific groups, subtrees, or for nested groups. Also a tree-view based on the UNIX command tree is included, which supports the listing of components and subtrees from the standard paths.

The main application is the usage by '**ctys-config -e**' for starting the default browser '**konqueror**' for browsing the configuration directories.

## 5 OPTIONS

**-d** <level>  
Debug.

**-D** <deepness-level>  
Display structure of configuration files with the given level of recursion deepness.

**-e** [<conf-file-list>|<path-list>]  
Edit one or multiple configuration files by **Emacs** or another preconfigured editor. The default display mode is **konqueror** in tab-view for multiple directories. When no argument is provided the default paths

```
'MYCONFPATH=${CTYS_LIBPATH}/conf/ctys'
```

and

'\${HOME}/.ctys'

are displayed. When a directory name and/or file list - is provided, these are searched for the relative path provided, first from current directory, than by using each **existing entry** within the standard path as a prefix. Absolute paths are just evaluated for providing a valid filename/pathname.

The default editor could be configured within the distribution specific configuration file by **CTYS\_CONFIGEDIT**. Currently preconfigured editors/starters are: Emacs, gvim, vim, konqueror, and nautilus.

**-F**

Display file structure as a directory-tree including contained files, the option **-D** controls the level option.

**-h**

Print help.

**-H <help-option>**

The extended help option is based on system interfaces for display of manpages, PDF and HTML documents. This comprises the man pages and installed manuals.

For additional help refer to the documents or type **ctys -H help**.

**-S**

Display directory structure of the configuration files with the given level of deepness in **-D** option.

**-V**

Version.

**-X**

Terse.

.

## 6 ARGUMENTS

ffs.

.

## 7 EXIT-VALUES

**0: OK:** Result is valid.

**1: NOK:** Erroneous parameters.

**2: NOK:** Missing an environment element like files or databases.

## 8 SEE ALSO

ctys manuals *ctys-user-maual-online*, *ctys-user-maual-print*

## 9 AUTHOR

Maintenance: <[acue\\_sf1@users.sourceforge.net](mailto:acue_sf1@users.sourceforge.net)>  
Homepage: <<http://www.UnifiedSessionsManager.org>>  
Sourceforge.net: <<http://sourceforge.net/projects/ctys>>  
Berlios.de: <<http://ctys.berlios.de>>  
Commercial: <<http://www.i4p.com>>



## 10 COPYRIGHT

Copyright (C) 2008, 2009, 2010, 2011 Ingenieurbuero Arno-Can Uestuensoez  
For BASE package following licenses apply,

- for software see GPL3 for license conditions,
- for documents see GFDL-1.3 with invariant sections for license conditions,

This document is part of the **DOC package**,

- for documents and contents from DOC package see  
'Creative-Common-Licence-3.0 - **Attrib: Non-Commercial, Non-Deriv**'  
with optional extensions for license conditions.

For additional information refer to enclosed Releasenotes and License files.

